



## ***MailXML Version 20.0***

# **System Messages Specification**

**May 3, 2017**

**Working Group Chair**

Shawn Baldwin, BCC Software

**Technical Director**

Shariq Mirza, Idealliance

**Editor:**

Dianne Kennedy, Idealliance

Copyright (c) International Digital Enterprise Alliance, Inc. [Idealliance] (2004 – 2017). All Rights Reserved.

Mail.dat is a registered trademark of Idealliance  
Mail.XML is a trademark of Idealliance



## Copyright and Legal Notices

© 2001 – 2017 International Digital Enterprise Alliance, Inc. All Rights Reserved.

This document may be downloaded and copied provided that the above copyright notice and this Notice are included on all such copies. This document itself may not be modified in any way, except as needed for the purpose of developing International Digital Enterprise Alliance, Inc. ("Idealliance") specifications. Use of the specification or standard set forth in this document shall not create for the user any rights in or to such specification or standard or this document, which rights are exclusively reserved to Idealliance or its licensors or contributors.

Use of this document and any specification or standard contained herein is voluntary. By making use of this document or any specification or standard contained herein, the user assumes all risks and waives all claims against Idealliance, its licensors and contributors. By making this document available, Idealliance is not providing any professional services or advice to any person or entity. Any person or entity utilizing this document or any specification or standard contained herein should rely upon the advice of a competent professional before using any such information.

NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, LEGALITY, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THIS DOCUMENT OR IN ANY SPECIFICATION OR STANDARD OR OTHER PRODUCT MADE AVAILABLE BY IDEALLIANCE. THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN AND INCLUDED IN ANY SPECIFICATION OR STANDARD OR OTHER PRODUCT OR SERVICE OF IDEALLIANCE IS PROVIDED ON AN "AS IS" BASIS. IDEALLIANCE DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY ACTUAL OR ASSERTED WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE.

IN NO EVENT SHALL IDEALLIANCE, ITS LICENSEES, CONTRIBUTORS OR THEIR RESPECTIVE OFFICERS, DIRECTORS, EMPLOYEES, AGENTS, REPRESENTATIVES, SUPPLIERS OR CONTENT OR SERVICE PROVIDERS BE LIABLE FOR DAMAGES OF ANY KIND, INCLUDING WITHOUT LIMITATION, DIRECT, INDIRECT, COMPENSATORY, SPECIAL, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION DAMAGES FROM DATA LOSS OR BUSINESS INTERRUPTION) EVEN IF MADE AWARE OF THE POSSIBILITY OF SUCH DAMAGES, WHETHER IN AN ACTION UNDER CONTRACT, TORT OR ANY OTHER THEORY, ARISING OUT OF OR IN CONNECTION WITH THE USE, INABILITY TO USE OR PERFORMANCE OF THIS DOCUMENT, THE SPECIFICATION OR STANDARD CONTAINED HEREIN, OR ANY OTHER DOCUMENT OR SPECIFICATION OR STANDARD MADE AVAILABLE BY IDEALLIANCE.

Some states do not allow the disclaimer or limitation of damages, so the disclaimers set forth above apply to the maximum extent permitted under applicable law.

Idealliance takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed or implicated with respect to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available. Idealliance does not represent that it has made any effort to identify any such rights. Information on Idealliance's procedures with respect to rights in Idealliance specifications can be found at the Idealliance website at [www.Idealliance.org](http://www.Idealliance.org). Copies of third-party claims of rights, assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification, can be obtained from the President of Idealliance at [patent-disclosure@Idealliance.org](mailto:patent-disclosure@Idealliance.org).

Idealliance requests interested parties to disclose any copyrights, trademarks, service marks, patents, patent applications, or other proprietary or intellectual property rights which may cover technology that may be required to implement this specification. Please address the information to the President of Idealliance at [patent-disclosure@Idealliance.org](mailto:patent-disclosure@Idealliance.org).

## Abstract

This document describes the messaging protocol for use by mailers and their consignees. The Mail.XML™ Transaction Protocol defines the roles and responsibilities of Shippers and Consignees and defines the format and method for message exchange. This messaging protocol is designed to be XML and Web-Services compliant and to work with FAST.

Mail.XML and Mail.dat are trademarks of Idealliance.

## About Mail.XML™

Mail.XML™ is bringing a paradigm change to the industry by increasing business function specific B2B (Business to Business) communication within the industry that supports automation and in the end enables cost avoidance and higher profits through improved competence and effectiveness of communication. Mail.XML is designed to increase efficiency and lower costs by removing many manual data entry processes and enabling quick near real time communication between business partners. Mail.XML currently supports container based scheduling, pick up and drop off business processes, as well as identifying different business entities responsible for performing different services such as quality of mailing, address correction, and delivery confirmation on a mailing.

The core focus of Mail.XML is communication between industry members and from industry to the final mail processing and delivery organization that delivers the mail to the end consumer, e.g., USPS.

In the next few versions of Mail.XML the focus moves across mailing supply chain channels, and includes advanced functions such as payment; automated verification; enabling first, second, and third party communication and incorporating presort planning, printing, and distribution processes.

## What's New in Mail.XML Version 20.0?

With this release, the Mail.XML Messaging Protocol moves to Version 20.0. This is a MAJOR release. This release supports ongoing USPS modernization and automation efforts for 2017.

Changes supported by MailXML 20.0 include:

- Currently, mailers cannot submit their own Campaign Titles (or Display Names, and Campaign Codes). These Campaign Titles, Campaign Codes and Campaign Display Name are generated by *PostalOne!* using a combination of eDoc fields and sent to Informed Delivery. This version of MailXML provides the ability for mailers to submit their own Campaign Display Name, Campaign Codes and Campaign Titles.
- MailXML V20 provides mailers with the ability to submit Campaign data absent or separate from the presort data and to issue an Informed Delivery Campaign Create Request.
- MailXML V20 provides mailers with the ability to withdraw a campaign with an Informed Delivery Campaign Delete Request.

**Note:** In order to modify a campaign, a user must first delete the campaign and then create a new campaign with the updated parameters. There is no message to update or modify a campaign at this time.

## About MailXML Schema Modularization

Today Mail.XML messages are grouped into 8 message types.

- Transportation Messages (TM)
- Mailing Messages (MM)
- Data Distribution Messages (DD)
- Dynamic Payment Template Messages
- Identification Messages (ID)
- Supply Chain Messages (SC)
- Informed Visibility (IV)
- System Messages
- Base: Shared simple types
- Definitions: Shared complex types and elements

The simple types shared across 2 or more modules are found in the Base schema. Likewise the shared definitions module contains complex type definitions and elements that are shared across 2 or more modules.

## MailXML Module Versioning Rules

The following versioning rules will be followed:

- The MailXML wrapper schema (\*.xsd) will always be given the next higher version number (or Errata designation) when any update is made to base, defs or any module. The name of the .xsd file will indicate the new version and the new version number will be used in the namespace and target declarations:  

```
xmlns:mailxml="http://Idealliance.org/Specs/mailxml20.0/mailxml"
targetNamespace="http://Idealliance.org/Specs/mailxml20.0/mailxml"
```
- When updates are made, only those modules that are updated will be given the next higher version number (or Errata letter designation).
- If updates are made to the base or defs, then the base and defs xsds will be given the next higher version number (or Errata designation) **and** all modules that call to them will also be given the next higher version number (or Errata designation).

For example:

- If the wrapper version is labeled as  
xmlns:mailxml="http://Idealliance.org/Specs/mailxml15.0A/mailxml" then at least one of the XSDs is at same version such as filename='mailxml\_15.0A.xsd' <- Errata A
- If the wrapper version is labeled as  
xmlns:mailxml="http://Idealliance.org/Specs/mailxml15.0B/mailxml" then at least one of the XSDs is at same version such as filename='mailxml\_15.0B.xsd' <- Errata B

- If the wrapper version is labeled as  
xmlns:mailxml="http://Idealliance.org/Specs/mailxml15.0/mailxml" then at least one of the XSDs is  
at same version such as filename = 'mailxml\_15.0.xsd' <- Major Version

## MailXML 20.0 XSD Modules:

The following MailXML XSD modules/namespaces are used:

- **mailxml\_tm.xsd**: This module contains all the transportation (or FAST) messages and the attributes, elements and complex types that are *unique* to these messages. **Namespace=mailxml tm:**
- **mailxml\_mm.xsd**: This module contains all the mailing messages (eDoc) and the attributes, elements and complex types that are *unique* to these messages. **Namespace=mailxml mm:**
- **mailxml\_iv.xsd**: This module contains informed visibility messages and the attributes, elements and complex types that are *unique* to these messages. **Namespace=mailxml iv:**
- **mailxml\_dd.xsd**: This module contains all the data distribution messages and the attributes, elements and complex types that are *unique* to these messages. **Namespace=mailxml dd:**
- **mailxml\_id.xsd**: This module contains all the identification messages and the attributes, elements and complex types that are *unique* to these messages. **Namespace=mailxml id:**
- **mailxml\_sc.xsd**: This module contains all the supply chain messages and the attributes, elements and complex types that are *unique* to these messages. **Namespace=mailxml sc:**
- **mailxml\_defs.xsd**: This module contains all the common definitions of attributes, elements and complex types that are used across two or more message types. **Namespace=mailxml defs:**
- **mailxml\_base.xsd**: This module contains simple types that are shared across two or more modules that make up mailxml. These can be considered a building block for any message group. **Namespace=mailxml base:**
- **mailxml.xsd**: This module contains the system messages of MailXML and is used to build custom profiles for MailXML. **Namespace=mailxml:**

## The Mail.XML™ 20 Messaging Documentation Set

The Mail.XML Messaging Specification has been organized into a set of documents. This *Schemas Specification* is one document in a set of documents that make up the Mail.XML Specification 16.0. Updates in this Specification are NOT backwardly compatible with previous versions. Other documents in the specification set include:

- *Mail.XML™ 20.0: Transportation Messaging Specification* documents all transportation messages
- *Mail.XML™ 20.0: Mailing Messaging Specification* documents all mailing messages
- *Mail.XML™ 20.0: Informed Visibility Specification* documents all informed visibility messages
- *Mail.XML™ 20.0: Data Distribution Messaging Specification* documents all data distribution messages
- *Mail.XML™ 20.0: Identification Messaging Specification* documents all identification messages
- *Mail.XML™ 20.0: Supply Chain Messaging Specification* documents all supply chain messages
- *Mail.XML™ 20.0: System Messaging Specification* documents all systems and fault messages
- *Mail.XML™ 20.0: Simple Types Specification* documents all simple types used across MailXML messages

- *Mail.XML™ 20.0: Common Definitions Specification* documents all shared elements and complex types.
- *Mail.XML™ 20.0: Schemas* contains the .XSDs that make up the MailXML Messaging Specification

## Table of Contents

Abstract.....	i
About Mail.XML™ .....	i
What’s New in Mail.XML Version 20.0?.....	i
About MailXML Schema Modularization .....	ii
MailXML Module Versioning Rules.....	ii
MailXML 20.0 XSD Modules: .....	iii
The Mail.XML™ 20 Messaging Documentation Set .....	iii
1    Index.....	1
2    Elements and Types .....	3

# 1 Index

## Elements

[DeliveryResponse](#)

[Fault](#)

[MessageResponseRetrievalRequest](#)

[MessageResponseRetrievalResponse](#)

[NotificationResponse](#)

[SystemVersionQueryRequest](#)

[SystemVersionQueryResponse](#)

## Complex types

[messageResponseNotAvailableResponseType](#)

[messageResponseRetrievalRequestType](#)

[messageResponseRetrievalResponseType](#)






## 2 Elements and Types


### element **DeliveryResponse**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>
properties	content complex
children	<a href="#">mailxml:UserLicenseCode</a> <a href="#">mailxml:MaildatJobID</a> <a href="#">mailxml:CustomerGroupID</a> <a href="#">mailxml:MailingGroupID</a> <a href="#">mailxml:PushMessageID</a> <a href="#">mailxml:DeliveryType</a> <a href="#">mailxml:ReturnInfo</a>
used by	element <a href="#">messageResponseRetrievalResponseType/QueryResults</a>
annotation	documentation Response sent to USPS by a customer when any delivery is pushed. For example when a delivery point validation delivery is pushed by USPS this response is returned by the receiver.

### element **DeliveryResponse/UserLicenseCode**

diagram			
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>		
type	<b>mailxml_base:userLicenseCodeType</b>		
properties	content	simple	
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	4	
	whiteSpace	preserve	


### element **DeliveryResponse/MaildatJobID**

diagram							
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml						
type	<b>mailxml_base:jobIDType</b>						
properties	content    simple						
facets	<table><tr><th>Kind</th><th>Value</th><th>Annotation</th></tr><tr><td>minLength</td><td>1</td><td></td></tr></table>	Kind	Value	Annotation	minLength	1	
Kind	Value	Annotation					
minLength	1						


## MailXML Version 20.0 Data Distribution Specification

	maxLength 8
	whiteSpace preserve


### element **DeliveryResponse/CustomerGroupID**

diagram			
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	<b>mailxml_base:s25</b>		
properties	minOcc 0	maxOcc 1	content simple
facets	Kind	Value	Annotation
	minLength 1		
	maxLength 25		
	whiteSpace preserve		


### element **DeliveryResponse/MailingGroupID**

diagram			
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	<b>xs:nonNegativeInteger</b>		
properties	content simple		

### element **DeliveryResponse/PushMessageID**

diagram			
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	<b>mailxml_base:s25</b>		
properties	minOcc 0	maxOcc 1	content simple
facets	Kind	Value	Annotation
	minLength 1		
	maxLength 25		
	whiteSpace preserve		

### element **DeliveryResponse/DeliveryType**


diagram			
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	<b>xs:string</b>		

properties	content	simple
------------	---------	--------

**element DeliveryResponse/ReturnInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml
type	<b>mailxml_defs:basicReturnInfoType</b>
properties	content complex
children	<b>mailxml_defs:ReturnCode</b> <b>mailxml_defs:ReturnDescription</b> <b>mailxml_defs:errorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>

**element Fault**

diagram													
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml												
properties	content complex												
children	<a href="#">mailxml:errorWarning</a>												
used by	element <a href="#">messageResponseRetrievalResponseType/QueryResults</a>												
attributes	<table><tr><th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>Annotation</th></tr><tr><td><a href="#">mailxml:TrackingID</a></td><td><b>mailxml_base:s20</b></td><td></td><td></td><td></td><td></td></tr></table>	Name	Type	Use	Default	Fixed	Annotation	<a href="#">mailxml:TrackingID</a>	<b>mailxml_base:s20</b>				
Name	Type	Use	Default	Fixed	Annotation								
<a href="#">mailxml:TrackingID</a>	<b>mailxml_base:s20</b>												
annotation	documentation A fault message.												

**attribute Fault/@TrackingID**

namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	mailxml_base:s20		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	

	whiteSpace	preserve
--	------------	----------


element **Fault/ErrorWarning**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>
type	<b>mailxml_defs:errorWarningType</b>
properties	content complex
children	<b>mailxml_defs:Code</b> <b>mailxml_defs:Severity</b> <b>mailxml_defs:KeyIDvalues</b> <b>mailxml_defs:SubmissionDate</b> <b>mailxml_defs:ErrorDescription</b> <b>mailxml_defs:Action</b> <b>mailxml_defs:TrackingID</b> <b>mailxml_defs:SubmitterTrackingID</b> <b>mailxml_defs:MailxmlDetail</b>


element **MessageResponseRetrievalRequest**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>
properties	content complex
children	<a href="#">mailxml:SubmittingParty</a> <a href="#">mailxml:SubmittingSoftware</a> <a href="#">mailxml:MessageResponse</a>
annotation	documentation Request to send responses once more when the response was interrupted by a system fault.

element **MessageResponseRetrievalRequest/SubmittingParty**

diagram						
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml					
type	<b>mailxml_defs:participantIDType</b>					
properties	content complex					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>				
	mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>				
	mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>				
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>				
	mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>				
	mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>				
	mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				

element **MessageResponseRetrievalRequest/SubmittingSoftware**

diagram						
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	content complex					

## MailXML Version 20.0 Data Distribution Specification

attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml_defs:SoftwareName	xs:string	required			
	mailxml_defs:Vendor	xs:string	required			
	mailxml_defs:Version	xs:string	required			
	mailxml_defs:ApprovalDate	xs:date				
	mailxml_defs:ApprovalKey	xs:string				

### element **MessageResponseRetrievalRequest/MessageResponse**

diagram						
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml					
type	<a href="#">mailxml:messageResponseRetrievalRequestType</a>					
properties	minOcc	1	maxOcc	unbounded	content	complex
attributes	Name	Type	Use	Default	Fixed	Annotation
	<a href="#">mailxml:TrackingID</a>	mailxml_base:s20	required			

### element **MessageResponseRetrievalResponse**

diagram	
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml
properties	content complex
children	<a href="#">mailxml:MessageResponseRetrievalAccept</a> <a href="#">mailxml:MessageResponseRetrievalReject</a>
annotation	documentation Response to the Message Response Retrieval Request that resends interrupted responses.


### element **MessageResponseRetrievalResponse/MessageResponseRetrievalAccept**

diagram						
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml					


## MailXML Version 20.0 Data Distribution Specification

e						
type	<a href="#">mailxml:messageResponseRetrievalResponseType</a>					
properties	content complex					
children	<a href="#">mailxml:QueryResults</a> mailxml_defs:QueryError					
attributes	Name <a href="#">mailxml:TrackingID</a>	Type mailxml_base:s20	Use required	Default	Fixed	Annotation

### element MessageResponseRetrievalResponse/MessageResponseRetrievalReject


diagram						
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>					
type	<a href="#">mailxml:messageResponseNotAvailableResponseType</a>					
properties	content complex					
children	<a href="#">mailxml:ReturnInfo</a>					
attributes	Name <a href="#">mailxml:TrackingID</a>	Type mailxml_base:s20	Use required	Default	Fixed	Annotation

### element NotificationResponse


diagram						
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>					
properties	content complex					
children	<a href="#">mailxml:UserLicenseCode</a> <a href="#">mailxml:MailingGroupID</a> <a href="#">mailxml:PushMessageID</a> <a href="#">mailxml:NotificationDate</a> <a href="#">mailxml:ReturnInfo</a>					
used by	element <a href="#">messageResponseRetrievalResponseType/QueryResults</a>					
annotation	documentation Standard response to a USPS notification to indicate the notification has been received.					




element **NotificationResponse/UserLicenseCode**

diagram			
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	<b>mailxml_base:userLicenseCodeType</b>		
properties	content simple		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	4	
	whiteSpace	preserve	


element **NotificationResponse/MaildatJobID**

diagram			
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	<b>mailxml_base:jobIDType</b>		
properties	content simple		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	8	
	whiteSpace	preserve	

element **NotificationResponse/CustomerGroupID**


diagram			
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	<b>mailxml_base:s25</b>		
properties	minOcc	0	
	maxOcc	1	
	content	simple	
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	25	
	whiteSpace	preserve	

element **NotificationResponse/MailingGroupID**


diagram			
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	<b>xs:nonNegativeInteger</b>		

properties	content simple
------------	----------------


**element NotificationResponse/PushMessageID**

diagram	
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml
type	<b>mailxml_base:s25</b>
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 25 whiteSpace preserve


**element NotificationResponse/NotificationDate**

diagram	
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml
type	<b>xs:date</b>
properties	content simple


**element NotificationResponse/ReturnInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml
type	<b>mailxml_defs:basicReturnInfoType</b>
properties	content complex
children	<b>mailxml_defs:ReturnCode mailxml_defs:ReturnDescription mailxml_defs:errorWarning mailxml_defs:ContainerErrorWarningBlock</b>


element **SystemVersionQueryRequest**

diagram	 The diagram shows a box labeled 'SystemVersionQueryRequest' connected to a circle with three dots. This circle is then connected to three stacked boxes: 'mailxml:TrackingID', 'mailxml:SubmittingParty', and 'mailxml:SubmittingSoftware'. Each of these three boxes has a small square icon with a plus sign in its top right corner, indicating they are optional or repeatable elements.
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>
properties	content complex
children	<a href="#">mailxml:TrackingID</a> <a href="#">mailxml:SubmittingParty</a> <a href="#">mailxml:SubmittingSoftware</a>
annotation	documentation Query request for the receiving system version information.

element **SystemVersionQueryRequest/TrackingID**

diagram	 A dashed box containing the text 'mailxml:TrackingID'.
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>
type	<b>mailxml_base:s20</b>
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 20 whiteSpace preserve


element **SystemVersionQueryRequest/SubmittingParty**

diagram	 The diagram shows a box labeled 'mailxml:SubmittingParty' connected to a larger box labeled 'mailxml_defs:participantIDType'. Inside this larger box, there is a section titled 'attributes' which contains a list of seven attributes: 'mailxml_defs:MailerID6', 'mailxml_defs:MailerID9', 'mailxml_defs:CRID', 'mailxml_defs:SchedulerID', 'mailxml_defs:MaildatUserLicense', 'mailxml_defs:ShippingAgentID', and 'mailxml_defs:ReceivingAgentID'. Each attribute is shown in a dashed box.
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>
type	<b>mailxml_defs:participantIDType</b>
properties	content complex


## MailXML Version 20.0 Data Distribution Specification

attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml_defs:MailerID6	mailxml_base:mailerID6Type				
	mailxml_defs:MailerID9	mailxml_base:mailerID9Type				
	mailxml_defs:CRID	mailxml_base:CRIDType				
	mailxml_defs:SchedulerID	mailxml_base:s12				
	mailxml_defs:MaildatUserLicense	mailxml_base:userLicenseCodeType				
	mailxml_defs:ShippingAgentID	mailxml_base:s12				
	mailxml_defs:ReceivingAgentID	mailxml_base:s12				

### element **SystemVersionQueryRequest/SubmittingSoftware**

diagram						
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml					
type	mailxml_defs:submittingSoftwareType					
properties	content complex					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml_defs:SoftwareName	xs:string	required			
	mailxml_defs:Vendor	xs:string	required			
	mailxml_defs:Version	xs:string	required			
	mailxml_defs:ApprovalDate	xs:date				
	mailxml_defs:ApprovalKey	xs:string				


### element **SystemVersionQueryResponse**

diagram	
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml
properties	content complex
children	<a href="#">mailxml:QueryResults</a> mailxml_defs:QueryError
used by	element <a href="#">messageResponseRetrievalResponseType/QueryResults</a>
annotation	documentation Response to a query for the receiving system version information.


element **SystemVersionQueryResponse/QueryResults**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>
properties	content complex
children	<a href="#">mailxml:TrackingID</a> <a href="#">mailxml:SubmitterTrackingID</a> <a href="#">mailxml:SoftwareStatus</a> <a href="#">mailxml:ReturnInfo</a>

element **SystemVersionQueryResponse/QueryResults/TrackingID**

diagram			
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>		
type	<b>mailxml_base:s20</b>		
properties	minOcc	0	
	maxOcc	1	
	content	simple	
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

element **SystemVersionQueryResponse/QueryResults/SubmitterTrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml												
type	mailxml_base:s20												
properties	<table><tr><td>minOcc</td><td>0</td></tr><tr><td>maxOcc</td><td>1</td></tr><tr><td>content</td><td>simple</td></tr></table>	minOcc	0	maxOcc	1	content	simple						
minOcc	0												
maxOcc	1												
content	simple												
facets	<table><tr><td>Kind</td><td>Value</td><td>Annotation</td></tr><tr><td>minLength</td><td>1</td><td></td></tr><tr><td>maxLength</td><td>20</td><td></td></tr><tr><td>whiteSpace</td><td>preserve</td><td></td></tr></table>	Kind	Value	Annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	Annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **SystemVersionQueryResponse/QueryResults/SoftwareStatus**

diagram						
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	content complex					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml_defs:SoftwareName	<b>xs:string</b>	required			
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

element **SystemVersionQueryResponse/QueryResults/ReturnInfo**

diagram						
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml					
type	<b>mailxml_defs:basicReturnInfoType</b>					
properties	minOcc	0				
	maxOcc	1				
	content	complex				
children	<b>mailxml_defs:ReturnCode mailxml_defs:ReturnDescription mailxml_defs:errorWarning mailxml_defs:ContainerErrorWarningBlock</b>					

complexType **messageResponseNotAvailableResponseType**

diagram						
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml					
children	<a href="#">mailxml:ReturnInfo</a>					
used by	element <a href="#">MessageResponseRetrievalResponse/MessageResponseRetrievalReject</a>					
attributes	Name	Type	Use	Default	Fixed	Annotation
	<a href="#">mailxml:TrackingID</a>	mailxml_base:s20	required			


attribute **messageResponseNotAvailableResponseType/@TrackingID**

namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	mailxml_base:s20		
properties	use required		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

element **messageResponseNotAvailableResponseType/ReturnInfo**

diagram			
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	mailxml_defs:returnInfoType		
properties	content complex		
children	mailxml_defs:ConsigneeFacility mailxml_defs:ErrorWarning mailxml_defs:ContainerErrorWarningBlock		


**complexType messageResponseRetrievalRequestType**

diagram						
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml					
used by	element <a href="#">MessageResponseRetrievalRequest/MessageResponse</a>					
attributes	Name	Type	Use	Default	Fixed	Annotation
	<a href="#">mailxml:TrackingID</a>	mailxml_base:s20	required			

**attribute messageResponseRetrievalRequestType/@TrackingID**

namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	mailxml_base:s20		
properties	use required		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

**complexType messageResponseRetrievalResponseType**

diagram						
namespace	http://idealliance.org/Specs/mailxml20.0/mailxml					
children	<a href="#">mailxml:QueryResults</a> mailxml_defs:QueryError					
used by	element <a href="#">MessageResponseRetrievalResponse/MessageResponseRetrievalAccept</a>					
attributes	Name	Type	Use	Default	Fixed	Annotation
	<a href="#">mailxml:TrackingID</a>	mailxml_base:s20	required			

**attribute messageResponseRetrievalResponseType/@TrackingID**


namespace	http://idealliance.org/Specs/mailxml20.0/mailxml		
type	mailxml_base:s20		
properties	use required		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	





element **messageResponseRetrievalResponseType/QueryResults**

diagram



namespace	http://idealliance.org/Specs/mailxml20.0/mailxml
properties	content complex
children	<a href="#">mailxml:Fault</a> mailxml_tm:AllApptCloseoutResponse mailxml_tm:ApptInductionCloseoutResponse mailxml_tm:CustomerSupplierAgreementQueryResponse mailxml_tm:DeliveryApptCancelCreateResponse mailxml_tm:DeliveryApptCancelResponse mailxml_tm:DeliveryApptContentRemoveResponse mailxml_tm:DeliveryApptCreateResponse mailxml_tm:DeliveryApptQueryResponse mailxml_tm:DeliveryApptShellCancelResponse mailxml_tm:DeliveryApptShellCreateResponse mailxml_tm:DeliveryApptShellUpdateResponse mailxml_tm:DeliveryApptStatusQueryResponse mailxml_tm:DeliveryApptTransportationUpdateResponse mailxml_tm:DeliveryApptUpdateResponse mailxml_tm:DeliveryContentCancelResponse mailxml_tm:DeliveryContentCreateResponse mailxml_tm:DeliveryContentQueryResponse mailxml_tm:DeliveryContentUpdateResponse mailxml_tm:GoodsReceiptResponse mailxml_tm:OpenApptQueryResponse mailxml_tm:PartnerApptQueryResponse mailxml_tm:PartnerContentAssignmentResponse mailxml_tm:PickupApptCancelResponse mailxml_tm:PickupApptCreateResponse mailxml_tm:PickupApptUpdateResponse mailxml_tm:RecurringApptQueryResponse mailxml_tm:StaleContentQueryResponse mailxml_tm:USPSDeliveryContentUpdatedQueryResponse mailxml_dd:ByForConflictQueryResponse mailxml_dd:DeliveryPointValidationQueryResponse mailxml_dd:AddressCorrectionQueryResponse mailxml_dd:DataQualityVerificationReportQueryResponse mailxml_dd:NixieDetailQueryResponse mailxml_dd:NonComplianceDataWithPostageOwedReportQueryResponse mailxml_dd:ScanSTCReconciliationQueryResponse mailxml_iv:ContainerVisibilityQueryResponse mailxml_iv:MPSVisQueryResponse mailxml_iv:StartTheClockQueryResponse mailxml_mm:BeginCombinedMailingResponse mailxml_mm:BundleDetailCancelResponse mailxml_mm:BundleDetailCreateResponse mailxml_mm:CloseMailingGroupResponse mailxml_mm:ComponentQueryResponse mailxml_mm:ComponentUpdateResponse mailxml_mm:ConsolidatedPeriodicalStatementCreateResponse mailxml_mm:ContainerBundleReportCancelResponse mailxml_mm:ContainerBundleReportCreateResponse mailxml_mm:ContainerBundleReportQueryResponse mailxml_mm:ContainerManifestCreateResponse mailxml_mm:ContainerManifestUpdateResponse mailxml_mm:ContainerManifestCancelResponse mailxml_mm:ContainerUpdateResponse mailxml_mm:CustomerMailReportCreateResponse mailxml_mm:EndCombinedMailingResponse mailxml_mm:InternationalPostageStatementCreateResponse mailxml_mm:InternationalPostageStatementQueryResponse mailxml_mm:InvoiceQueryResponse mailxml_mm:MailPieceCancelResponse mailxml_mm:MailPieceCreateResponse mailxml_mm:MailPieceUpdateResponse mailxml_mm:MailingGroupQueryResponse mailxml_mm:ManifestCreateResponse mailxml_mm:ManifestCancelResponse mailxml_mm:ManifestPaymentExtractQueryResponse mailxml_mm:OpenMailingGroupResponse mailxml_mm:PaymentMessageQueryResponse mailxml_mm:PeriodicalStatementCreateResponse mailxml_mm:PeriodicalStatementQueryResponse mailxml_mm:PostageStatementCancelResponse mailxml_mm:PostageStatementCreateResponse mailxml_mm:PostageStatementQueryResponse mailxml_mm:PostageStatementStatusQueryResponse mailxml_mm:QualificationReportCreateResponse mailxml_mm:QualificationReportDetailCreateResponse mailxml_mm:QualificationReportQueryResponse mailxml_mm:QualificationReportSummaryCreateResponse mailxml_mm:ReconciliationReportQueryResponse mailxml_mm:SummaryZipDestinationReportCreateResponse mailxml_mm:TMSDataLoggerQueryResponse mailxml_id:CastofCharactersCancelResponse mailxml_id:CastofCharactersCreateResponse mailxml_id:CastofCharactersUpdateResponse mailxml_id:CustomerRelationIdentifyQueryResponse mailxml_id:CustomerRelationIdentifyUpdateResponse mailxml_id:IncentiveEnrollmentCreateResponse mailxml_id:USPSRIDCreateValidateResponse mailxml_id:USPSMIDCreateValidateResponse mailxml_sc:ContainerStatusQueryResponse mailxml_sc:OriginalContainerLinkageCancelResponse mailxml_sc:OriginalContainerLinkageCreateResponse mailxml_sc:PostageAdjustmentCreateResponse mailxml_sc:SiblingContainerCancelResponse mailxml_sc:SiblingContainerCreateResponse <a href="#">mailxml:DeliveryResponse</a> <a href="#">mailxml:NotificationResponse</a> <a href="#">mailxml:SystemVersionQueryResponse</a> <a href="#">mailxml:ReturnInfo</a>

element **messageResponseRetrievalResponseType/QueryResults/ReturnInfo**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml20.0/mailxml">http://idealliance.org/Specs/mailxml20.0/mailxml</a>
type	<b>mailxml_defs:basicReturnInfoType</b>
properties	minOcc 0 maxOcc 1 content complex
children	<b>mailxml_defs:ReturnCode</b> <b>mailxml_defs:ReturnDescription</b> <b>mailxml_defs:errorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>