



Digital Press Certification Application Data Sheet

Canon imagePRESS Server B5000/B4000

Canon imagePRESS C10000VP/C8000VP

Note: Certification is in accordance with IDEAlliance Digital Press Certification Program v2.2

The IDEAlliance Print Properties Digital Print Working Group has established a certification process for digital production presses (xerographic/inkjet). The following information is intended to assist printers and customers in understanding the printing conditions and how they were achieved and/or to replicate these results on a similar system.

I. Manufacturer

Electronics for Imaging
6750 Dumbarton Circle
Fremont, CA 94555

II. Product Name

Canon® imagePRESS C10000VP/C8000VP / imagePRESS Server B5000/B4000 / Fiery FS200 Pro /
EFI Laser Proof Paper XF130 Semimatt 130 gsm

Heather Blakley 9/4/15 6:38 PM

Deleted: , FS200

III. Overview

Flexible and scalable Fiery servers integrate into any print environment, deliver high performance, image with industry standard precision, and produce accurate color for all environments.

- Deliver professional color and consistency from anyone.
- Color Profiler Suite option provides tools and features to match press standards and monitor colorimetric conformance.
- Decreases set-up time, reduces errors, and costly reprints dramatically.
- Provides high return of investment with a flexible, scalable product line.
- Integrates into all print environments because of its open platform technology.
- Supports variable data printing.

IV. System Components and Printing Procedure

DFE: Canon imagePRESS Server B5000
Canon imagePRESS Server B4000
Software: Fiery Command WorkStation 5.7
Fiery Color Profiler Suite 4.7
X-Rite ColorPort
Measurement: EFI ES-2000 Spectrophotometer
Eye-one iSis XL
Printer: Canon imagePRESS C10000VP/C8000VP Digital Press
Paper: EFI Laser Proof Paper XF130 Semimatt 130 gsm

Warm-up printer and perform calibration processes

The printer should first be in a warmed-up by printing at least 25 full coverage sheets. Next proceed to the printer touchscreen and perform the Auto Gradation Adjustment (AGA) procedures using the recommended Hammermill Color Copy Digital 28lb (105 gsm) paper for the US engine region. Once complete, proceed to Command Workstation.

Use of the EFI ES-2000 Spectrophotometer is recommended for Fiery calibration. Go to Device Center : General : Tools : Calibrate : Preferences to check that the following properties are set:

- Measurement method : EFI ES-2000
- Patch layout : 51 Unsorted Patches

Next, choose Calibrate : Manage calibration settings. To create a new calibration set, click "Create New...", and using "Coated (70-209 gm²)" as your basis for printing properties. Set Name and Recommend Paper for the new calibration set, being sure to set the following job properties:

- Media : Media type : 2-sided coated 3 (129-150 g/m²)
- Image : Printer's halftone : Standard

Measure the calibration sheet that is printed. Save the newly created calibration set, and (placeholder) output profile based off any of the factory profiles. A new custom profile will be created using the calibration setting associated with this profile.

Create an output profile

The following print properties are used to capture the printer's linearized state for creating an ICC profile. Any other settings should be set to the server's factory defaults with the exception of media tray settings. Print the Digital Press Form 1 PDF bypassing color conversion.

- Media : Media type : 2-sided coated 3 (129-150 g/m²)
- Image : Printer's halftone : Standard
- Color : Expert Settings : Color Input : CMYK/Grayscale : Bypass conversion
- Color : Expert Settings : Gray & Black Processing: Gray : CMYK : Off
- Color : Expert Settings : Gray & Black Processing : Black : Black text and graphics : Normal
- Color : Expert Settings : Output : *[Newly created placeholder output profile name]*

Heather Blakley 9/4/15 6:40 PM

Comment [1]: How should it be written?
I1iSis XL

Next measure the IT8.7/4 section of the press form with ColorPort, using an Eye-one iSis XL, including UV measurements (M0 mode). Save the measurements in the CGATS format, conversion none (XRGGA).

Note: While Fiery Color Profiler Suite recognizes this measurement file format, the line with "DEVICALSTD XRGGA" present in certain measurement file headers should be commented out or deleted. This allows the ColorPort measurement file to conform to the CGATS file specification and be successfully read by Fiery Color Profiler Suite.

Create a printer profile with Fiery Color Profiler Suite. Skip to the "Convert Measurements to Profile" module. Select the Import settings option, and select the "Generic CMYK" profile preset. Save the new output profile to the server or as a local file to import later.

Important : Associate this output profile with the newly created calibration set when importing into Command WorkStation.

If difficulties meeting the colorimetric tolerances of Section 2.2 are encountered, it is recommended that a press technician be consulted to ensure the press is performing in peak condition, increasing toner mass can increase the press's gamut. Re-create an ICC profile from new measurements if press service has been preformed.

Print the Digital Press Forms

Use the following set of print properties as a baseline for printing the press forms. There are individual exceptions for some of the press forms that will be noted.

- Media : Media type : 2-sided coated 3 (129-150 g/m2)
- Image : Printer's halftone : Standard
- Color : Expert Settings : Color Input : CMYK/Grayscale : GRACoL2006 Coated1 (EFI)
- Color : Expert Settings : Color Input : CMYK/Grayscale : Processing method : Full (Output GCR)
- Color : Expert Settings : Color Input : CMYK/Grayscale : Black point compensation : On
- Color : Expert Settings : Color Input : CMYK/Grayscale : Paper simulation : On
- Color : Expert Settings : Gray & Black Processing: Gray : CMYK : Off
- Color : Expert Settings : Gray & Black Processing : Black : Black text and graphics : Normal
- Color : Expert Settings : Output : *[newly created output profile]*

For Digital Press Form 3 (Section 2.5), it is advised to recalibrate the engine using Fiery Calibrator prior to the 1-hour and 24-hour test prints depending on the amount of printer usage. Create a new color bar in Device Center : Color Setup : Control Bar : Create New...

Add the following properties:

Color bar name : Date Time

Job Information : Job Title

Job Information : Date/Time

For Digital Press Form 4 (Section 2.6),

- Image : Advanced smoothing : Level 2

For Digital Press Form 6 (Section 2.8, 2.9, 2.10) turn off color processing.

- Color : Expert Settings : Color Input : CMYK/Grayscale : ColorWise OFF

V. Finishing Procedures (Optional)

VI. Additional Data (Optional)

Users can also achieve this match using Color Profiler Suite (CPS) with EFI ES-2000. Launch CPS and select Create Profile Printer Module. Select "Print Patches". Specify 1617 random (CGATS IT8.7/4) patch set. Select "Use Current Calibration", under Print Patches : Expert Settings. Set Print Properties as specified in the "Create an output profile" section above. Measure patches with the EFI ES-2000 as directed by the Fiery Printer Profiler. Import Settings from the server or use Generic CMYK and custom settings as necessary.

Device Linker "Match to a Standard" iterative profile enhancement can be used to refine color match precision if desired.